


NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U. S. space program and to encourage their commercial application. Copies are available to the public from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

Electrically Conductive Fibers Thermally Isolate Temperature Sensor



The problem:

To devise a rugged mounting that will provide thermal isolation and an electrical path for an unbacked thermal sensor.

The solution:

Suspend the sensor in the center of a plastic mounting ring from four plastic (e.g., acrylic resin) fibers, two of which are coated with an electrically conductive material and connected to electrically conductive coatings on the ring.

How it's done:

Two sections of the upper surface of the mounting ring, made of insulating material, are coated with an electrically conductive material. Two of the plastic fibers are partially coated with a thin electrically conductive film and are secured both to conductive coatings on the sensor and the two electrically conductive TOP VIEW OF ASSEMBLY

sections of the mounting ring. Electrical leads to an external circuit are connected to these sections. Two untreated (nonconductive) fibers are secured to the underside of the sensor, which is then coated with a film of insulating material (e.g., selenium). The ends of these nonconductive fibers are secured to the mounting ring with a suitable adhesive.

Both pairs of fibers provide a vibration- and shockproof support as well as thermal isolation for the sensor. The pair coated with an electrically conductive film offers a much higher thermal resistance than a solid conductor.

Note:

This type of sensor assembly may be permanently installed in large pieces of electrical equipment, such as in power stations, for temperature measurement under conditions where the time constant of the sensor is not critical.

(continued overleaf)

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States

Government assumes any liability resulting from the use of the information contained in this document, or warrants that such use will be free from privately owned rights.

... SRARV - 1495

Patent status:

Title to this invention has been waived under the provisions of the National Aeronautics and Space Act [42 U.S.C. 2457 (f)], to the Barnes Engineering Company, 30 Commerce Road, Stamford, Connecticut.

Source: Bruce Norton and Russel DeWaard of Barnes Engineering Company under contract to Goddard Space Flight Center (GSFC-456)